



# MEASURED PERFORMANCE OF THE LHC COLLIMATORS LOW LEVEL CONTROL SYSTEM

**Dr. A. Masi**

**CERN, Switzerland**

**EN Dept, STI group**

**alessandro.masi@cern.ch**

# Outline

- The LHC collimation system
- Motorization solution
- Control requirements
- Low-level control system
- Measured performances
- Conclusions



# Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## The importance of the collimators in the LHC

The LHC nominal beam energy is equivalent to:

One US aircraft carrier at  
11 knots



A mis-stereed beam can provoke:

1. Damage to the machine

The energy in the two LHC beams is sufficient to melt almost 1 ton of copper

2. Quenches:

For example, local transient loss of  $4 \times 10^7$  protons at 7 TeV

**The LHC collimation system has to protect a machine of 2 billions \$ and reduce noise to the LHC experiments absorbing particles out of the nominal beam core**








# Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## The LHC collimators

A collimator has two parallel jaws  
Each jaw is controllable in position  
and angle



The jaws positioning accuracy is function of the beam size (1/10 beam size). At top energy 20 um accuracy is required






# Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

# The LHC collimators system




**The collimation system  
is based on different  
collimators types  
and**

**up to 108 collimators  
distributed over 6  
points in the machine**

**Jaw positions are  
correlated  
primary – secondary–  
tertiary**

**Also during  
movements  
they have to stay in  
sync within few ms**






## Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

# The Motorization Solution



Side view at one end



**Collimator Axes Motor type:** Stepping Motors Controlled in open loop ( 4 for the jaws axes + 1 for the vertical axis)

**Steps Loss Detection:** Resolvers ( 4 for the jaws' axes)

**Positions Survey:** LVDT sensors in redundant number (5 for the axes absolute position and 2 for the jaws' gap)



## Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## The control requirements

555 stepping motor Axes to control:

- **Jaws positioning accuracy: fraction (1/10...) of the beam size (200 µm!!).**
- **Synchronization between the two motors of the same jaw: much less than 1 ms to reduce vibrations**
- **Motion profiles: jaws in different collimators need to be locked for more than 30 minutes to movement functions sent by a central supervisory application.**  
The motion start is provided by a Trigger sent via optical fiber
- **Response delay to a digital trigger: < 1ms**
- **Synchronization between all the 555 collimators motors all along a motion profile: < 10 ms**



## Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## The control requirements

750 positioning sensors to survey:


- **Survey frequency:** position sensors have to be read at least at 100 Hz to check in Real-Time that the actual position lies within a given limit function
- **Synchronization between survey process and profile generation:** few ms
- **Low level rack dimensions:** maximum 400 mm deep. Limited space in the rack (in one 400 mm deep rack we need to install the controls for at least two collimators)
- **Reliability:** since collimators protect the machine the first requirement of the control system is reliability



# Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

# The control architecture





# Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions


## Control system software architecture

The new Front-End Software Architecture (FESA) is a comprehensive framework for designing, coding and maintaining LynxOS/Linux equipment-software that provides a stable functional abstraction of accelerator devices

See details at:  
<http://project-fesa.web.cern.ch/project-fesa>

network support TCP/IP  
(See details at <http://dim.web.cern.ch/dim/>)

The DIM Server library was successfully compiled for Pharlapp






# Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## The control system synchronization solution






# Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

# MDC hardware architecture






# MDC RT tasks architecture

## Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions






## Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- **Low Level Control System**
- Measured performances
- Conclusions

# PRS hardware architecture






# Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

# PRS RT tasks architecture






## Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## MDC measured performances



**Trigger delay ~ 120 us**

**Start jitter: 4 us**

**Stop jitter: 50 us**

**Profile duration: ~30 minutes**

Determined by local clock




## Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## PRS measured performances

21 LVDTs are read in less than 1 ms with a negligible jitter. The requirement about 100 Hz reading frequency is easily satisfied






# Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## PRS measured performances

PRS Reading uncertainty: **0.3  $\mu\text{m}$  typical**



**Distribution of 658 LHC Collimators LVDT reading uncertainty evaluated on 100 repeated measurements at 1 Hz**



A. Masi, R. Losito, S. Redaelli,

Measured Performance of the LHC Collimators Low-level control system, ICAL-EPS 2009



# Road Map


- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## PRS measured performances

### PRS long term stability

The main causes of reading drift are the temperature and DAQ card stability

- LVDT temperature sensitivity:  $1 \text{ um/ } ^\circ\text{C}$  (we have PT100 inside the sensor. We could compensate this drift)
- PRS temperature sensitivity: Thermal cycles showed that the reading drift produced by temperature excursion on the only PRS is actually negligible compared to that of the sensor
- Daq Card stability: according to the spec. less than 1 um drift per year is expected



Drift Distribution of 85 LHC Collimators LVDT over 3 weeks






## Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

# PRS measured performances



**Survey start jitter: 1.8 ms**

**Survey stop jitter: 2 ms**

**Survey profile duration : ~30 minutes**

- The jitter parameters refer to the monitoring profiles of all the 108 collimators
- The values in the table represent average values on 30 repeated threshold profiles.
- The PRS timestamps are used to perform these measurements




# Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## Global system measured performances


### Motion profiles positioning accuracy

Taking as the test profile the 5 TeV energy ramp, we define for each collimators' axis over 30 repeated executions



75 collimators: Synchronized ramps to 5 TeV  
(Nominal Beta functions)

- **positioning systematic error:** the average of the max error (i.e. difference between the LVDT reading and the requested position) over all the profile
- **positioning repeatability** as the standard deviation of the max error over all the profile



Reproducibility of the collimators axes positioning over 1 day and 11 profiles



## Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## Some installation pictures



A. Masi, R. Losito, S. Redaelli,

Measured Performance of the LHC Collimators Low-level control system, ICALEPS 2009





## Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## Some installation pictures





## Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

# Conclusions

	Required	Measured
Positioning repeatability	$\pm 20 \text{ }\mu\text{m}$	below 10 $\mu\text{m}$
Motion profiles synchronization	few ms	$\sim 100 \text{ }\mu\text{s}$
Synchronization between axes of the same jaw	below 1 ms	few us
Survey profiles synchronization	few ms	$\sim 2 \text{ ms}$
Position sensors reading accuracy	few $\mu\text{m}$	below 1 $\mu\text{m}$
Position sensors long term stability	$\pm 10 \text{ }\mu\text{m}$	$\pm 10 \text{ }\mu\text{m}$



# Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

## Acknowledgements

We Thank R. W. Assmann, M. Jonker, M Sobczak for the long discussions on the architecture of the collimation control system

Our colleagues of the EN/STI/ECE section, in particular M. Donze, P. Gander, J. Lendaro and M. Martino for the fruitful collaboration on the implementation of the system and the characterization

We are indebted to NI for the precious support received. In particular the System Engineering Group (Doug, Brent and Christian) and all the R&D people that were involved in this project as well as the Big Physics team (Stefano, Murali, Joel, Christian).

Last but not least Chris and Giuseppe





## Road Map

- The LHC collimation system
- Motorization solution
- Control requirements
- Low Level Control System
- Measured performances
- Conclusions

Thank you very much  
for your attention

